Wolfvision VZ-C3D Ceiling Visualiser

Bringing Reality Closer in 3D



The world's first 3D Visualiser system, a stereoscopic 3D 'live' presentation solution. The ceiling mounted VZ-C3D features two high precision lenses and an onboard stereoscopic mixer enabling stunning 'live' high definition 3D images viewed in realtime via a suitable projector or 3D-enabled display screen.

Key Features

Switchable 3D / 2D modes

Switch between 3D and 2D modes providing maximum flexibility in the range of materials displayed. You can also control the extent of the 3D effect using adjustable depth control, to select how far the 3D image appears 'in front' of or 'behind' the display screen.

Large Zoom Range and High Depth of Focus

A very high depth of focus is provided, benefiting you and your students when working with 3D objects. The two high precision wide-angle camera lenses with 15x optical and 4x digital zoom, allows yours objects / sheets be picked up in full resolution and high detail, for you and your class to not miss any details.

100% Reflection-Free with Intuitive Synchronised Lightfield

The advanced light system ensures no light from the Visualiser is reflected back into the camera with the entire working surface is always 100% reflection-free. Plus, the lightfield is the same size as the pick-up area, and adjusts with the zoom of the camera, so is always the perfect match.

Powerful High Definition Cameras

With two state of the art CMOS cameras with native 1080p HD resolution and 30 frames per second in both 3D and 2D modes, with 980 lines resolution are visible in every part of the picture, giving your objects clarity on your project or interactive white board.

Perfect Illumination with Shadow-Free Images

The light layout allows the whole recorded picture to be perfectly illuminated, including hollow or complex 3-D objects - even on the inside. Located next to each other, the camera and the light projector follow the same path, almost eliminating shadows. Even during presentations, when it is often necessary to write on the working surface or to point to a detail with a finger or a pencil, shadows don't cover up any details in your image.

Product Specification

Wolfvision VZ-C3D

Features

Camera 2 x 1-CMOS 1/3"

2-dimensional / 2D and 3D

3-dimensional

Pictures per second 30 fps in 2D and 3D Mode

Native Effective Pixels $2 \times 1920 \times 1080$ Native pixels of image $2 \times 1920 \times 1080$

Pixels processed per 124,416,000

second

Colour reproduction / sRGB colour precision

precision

Native signal output 1080p HD (1920 x 1080) in 2D and 3D mode,

with 3D modes: frame packing, top and

bottom, side by side, page flip, line alternative,

left/right and right/left

Resolution (measured) 980 lines

Brightness Control Automatic and manual
White balance Automatic and manual

adjustment

Autofocus / Speed Yes (continuously working, high speed)

Synchronised lightfield Yes (for easy positioning of objects)

On screen menu/help Yes

Firmware updates via LAN, vSolution Link Pro software

Lens 2 camera wide-angle zoom lenses and 1 light

zoom lens

Total Zoom x60 Total Zoom (x 15 optical, x 4 digital)

Max. object height on working surface

Max. width pick-up area on working surface

Min. width pick-up area on working surface

Shadow-free

illumination

Illumination of hollow

objects

Light source

vSolution Link Pro

software

Video recording

including audio

User programmable

presets

1.7m (depending on installation height)

861 mm - 1886 mm (depending on installation

height)

78mm - 174 mm (depending on installation

height)

Yes

Yes

Yes, high output, low power, 30,000 hours.

Yes, remote management & firmware updates

Yes, to 500GB SSD storage

Yes, 3





Product Specification

Wolfvision VZ-C3D

Reflection free are on

Entire working surface

Yes (Motion JPEG)

work surface

HDMI out

Ethernet / LAN port

LAN web interface

LAN streaming modes

(Multicast and

unicast)

vSolution App Yes, wireless control via mobile device

X

Yes

compatible

Advanced controlling Yes

with professional

protocol via LAN

Weight 5.2kg

Infrared remote control Yes. Optional external receiver (with 10m cable

and status LED)

Ceiling Mount Included

Power Internal power supply, multi range 100 - 240 V

65W

Power Consumption 39W

Warranty 5 years



















