Wolfvision VZ-C6 Ceiling Visualiser

Driving Knowledge Creation



The ceiling-mounted VZ-C6 ensures that nothing obstructs the view between the presenter and the audience during a presentation. It comes with a native 1080p HD camera, Synchronized Lightfield, and multimedia HD recording functionality.

Key Features

High Resolution Camera

A high definition 1-CMOS camera with 30 frames per second, sRGB colour precision and 1080p HD native image format gives 980 lines of visible resolution in every part of the picture.

Large Zoom Range and High Depth of Focus

An impressive zoom range of 48x (12x optical and 4x digital) allows for close-up zooming for high detail, while large objects also fit within the pick-up area. The Wide-angle lens has a very high focus depth ensuring that at high magnification, images are always sharp from top to bottom.

Easy to use

Most settings are automatically adjusted, so you don't need to change settings on the fly, so you can adjust the zoom for your optimised viewing experience, and the camera will do the rest.

100% Reflection-Free with Intuitive Synchronised Lightfield

The advanced light system ensures no light from the Visualiser is reflected back into the camera with the entire working surface is always 100% reflection-free. Plus, the lightfield is the same size as the pick-up area, and adjusts with the zoom of the camera, so is always the perfect match.

Recording made easy

Onboard recording functionality enables entire presentations to be captured including the audio, providing a quick and easy solution for in-house recording of training videos or lecture content.

Perfect Illumination with Shadow-Free Images

The light layout allows the whole recorded picture to be perfectly illuminated, including hollow or complex 3-D objects - even on the inside. Located next to each other, the camera and the light projector follow the same path, almost eliminating shadows. Even during presentations, when it is often necessary to write on the working surface or to point to a detail with a finger or a pencil, shadows don't cover up any details in your image.



Product Specification

Wolfvision VZ-C6

Camera	1-CMOS 1/3", 30 frames per second
Effective Pixels	1920 x 1080

Native Signal Output 1080p HD (1920 x 1080)

Converted output UXGA (1920 x 1200) / SXGA (1280 x 1024) /

signals (4:3 & 5:4) XGA (1024 x 768) / SVGA (800 x 600)

Converted Widescreen WUXGA (1920 x 1200) / WXGA (1280 x 800) /

output signals 720p HD (1280 x 720)

(16:9 and 16:10)

Features

Resolution (measured) 980 lines

resolution sRGB colour precision

Brightness Control & White Balance

Adjustment

Focusing Modes High speed Continuous Auto Focus /

Manual Focus

Automatic and Manual

Synchronised lightfield Yes

(for easy positioning

of objects)

Live to Freeze Yes (Picture-in-Picture & Side by Side)

Comparison

On-screen Menu & Help Yes

Firmware Updates Yes via USB, LAN or USB Stick

Zoom x 48 Total Zoom (x 12 optical & x 4 digital)

Lens Wide angle

Max object height on No limit

working surface

Max. pick-up area on working surface

Min. pick-up area on

working surface

Shadow-free

illumination

Illumination of hollow

objects

Light source

vSolution Link Pro

software

UVC drive

User programmable

presets

Reflection free are on

work surface

vSolution App

Compatible

Video recording

including audio

Image Memory

Browsable image

memory

904 - 1748 mm (depending on installation height)

89 - 138 mm (depending on installation height)

Yes

Yes

Yes, high output, low power, 30,000 hours.

Yes, remote management & firmware updates

Yes, for Windows, Linux and macOS

Yes

Entire working surface

Yes, wireless control via mobile app

Yes - 720p HD upto 30fps / AVI container /

H.264 codec / .AVI file extension

8GB Internal memory + additional storage via

USB device (stick or external hard drive)

Yes, scrollable thumbnails + 1 larger preview

image



Product Specification

Connectivity

HDMI in x 2

HDMI out

RGB

X **LAN** port x 1, IP addressable 10/100 Mbps

Yes

USB Device port x 1 **USB Host ports** x 2

Audio Line In x 1

Audio Line Out x 1

IR-Extern χl

External computer Yes, 2 x HDMI (DVI or Display Port via optional adaptor or cable)

input / Input Switch

Seemless cross fading

between sources

LAN Streaming Modes

Advanced controlling

with professional

protocol

Dimensions

Weight

Infrared remote control

Ceiling Mount

Power

Power consumption

Warranty

H.264 / Motion JPEG /

RTP Motion JPEG including audio

Yes, via LAN and USB

1 478mm x W125mm x H178mm

4.8kg

Yes (Optional external receiver with 10m cable

Wolfvision VZ-C6

and status LED)

Included

Internal Power supply, multi range 100 - 240V

Max 50W, adjustable standby power

consumption

5 Years



Shadow-free pick-up area

















